

1 **THREE-DIMENSIONAL MOLDED BLADE AND METHOD FOR**  
2 **MANUFACTURING THE BLADE**

3 **BACKGROUND OF THE INVENTION**

4 **1. Field of the Invention**

5 The present invention relates to a three-dimensional molded blade  
6 and the method for manufacturing the three-dimensional molded blade.

7 **2. Description of the Related Art**

8 A conventional blade for a ceiling fan comprises a plurality of sheet  
9 material laminated with each other. However, the conventional blade lacks  
10 variation in the shape and pattern, thereby decreasing the aesthetic quality of  
11 the conventional blade.

12 **SUMMARY OF THE INVENTION**

13 The present invention is to mitigate and/or obviate the disadvantage  
14 of the conventional blade for a ceiling fan.

15 The primary objective of the present invention is to provide a  
16 three-dimensional molded blade and the method for manufacturing the blade,  
17 wherein the molded layer forms an arch-shaped structure on the surface of the  
18 substrate, so that the molded blade has a greater structural support strength  
19 with a light weight, thereby decreasing consumption of rotational energy of the  
20 ceiling fan.

21 Another objective of the present invention is to provide a  
22 three-dimensional molded blade and the method for manufacturing the blade,

1 wherein the molded blade is manufactured by an automatic process without  
2 needing the manual work, so that the molded blade can be produced at a higher  
3 speed with a higher quality.

4 A further objective of the present invention is to provide a  
5 three-dimensional molded blade and the method for manufacturing the blade,  
6 wherein the molded blade can be produced rapidly, easily and conveniently  
7 without needing the manual work, thereby decreasing costs of fabrication.

8 A further objective of the present invention is to provide a  
9 three-dimensional molded blade and the method for manufacturing the blade,  
10 wherein the pattern of the molded layer can be changed arbitrarily by variation  
11 the shape of the cavity of the shaping mold, thereby enhancing aesthetic  
12 quality and variation of the molded blade.

13 In accordance with the present invention, there is provided a method  
14 for manufacturing a three-dimensional molded blade, comprising a press  
15 molding process including:

16 providing a shaping mold having a top formed with a  
17 three-dimensional cavity;

18 placing a molded layer in the shaping mold and located above the  
19 cavity;

20 inserting a press mold into the shaping mold; and

1           heat pressing the molded layer between the press mold and the  
2   shaping mold during a period of time, thereby forming a three-dimensional  
3   molded layer in the cavity of the shaping mold.

4           Further benefits and advantages of the present invention will become  
5   apparent after a careful reading of the detailed description with appropriate  
6   reference to the accompanying drawings.

7                           **BRIEF DESCRIPTION OF THE DRAWINGS**

8           Fig. 1 is a perspective view of a three-dimensional molded blade in  
9   accordance with the preferred embodiment of the present invention;

10          Fig. 2 is a side plan cross-sectional view of the three-dimensional  
11   molded blade as shown in Fig. 1;

12          Fig. 3 is a flow chart of a method for manufacturing the  
13   three-dimensional molded blade in accordance with the preferred embodiment  
14   of the present invention;

15          Fig. 4 is a schematic cross-sectional view showing fabrication of the  
16   three-dimensional molded blade as shown in Fig. 1;

17          Fig. 5 is a schematic cross-sectional view showing fabrication of the  
18   three-dimensional molded blade as shown in Fig. 1;

19          Fig. 6 is a schematic cross-sectional view showing fabrication of the  
20   three-dimensional molded blade as shown in Fig. 1; and

21          Fig. 7 is a schematic cross-sectional view showing fabrication of the  
22   three-dimensional molded blade as shown in Fig. 1.

## **DETAILED DESCRIPTION OF THE INVENTION**

Referring to the drawings and initially to Figs. 1 and 2, a three-dimensional molded blade 10 in accordance with the preferred embodiment of the present invention is available for a ceiling fan and comprises a three-dimensional molded layer 11, and a substrate 12 mounted on a bottom of the molded layer 11. Thus, the whole surface of the molded blade 10 produces a three-dimensional molded visible sensation.

Referring to Figs. 3-7 with reference to Figs. 1 and 2, a method for manufacturing the molded blade 10 comprises the following steps:

press molding process 20;

bonding process 30; and

cutting process 40.

In the press molding process 20, a shaping mold 21 is provided, wherein the shaping mold 21 has a top formed with a three-dimensional cavity 210. Preferably, the shaping mold 21 is made of a flexible material, such as the rubber, and is heated to the temperature of 180°C. Then, a sheet-shaped molded layer 11 is placed in the shaping mold 21 and located above the cavity 210. Then, a press mold 22 is heated to the temperature of 100°C, and is inserted into the shaping mold 21 as shown in Fig. 4, so that the molded layer 11 is heat pressed (the step 23) between the press mold 22 and the shaping mold 21 during a period of time (about three minutes), thereby forming a

1 three-dimensional molded layer 11 (the step 24) in the cavity 210 of the  
2 shaping mold 21 as shown in Fig. 5.

3 In the bonding process 30, the three-dimensional molded layer 11 is  
4 removed from the cavity 210 of the shaping mold 21, and is bonded on a  
5 substrate 12, so that the three-dimensional molded layer 11 is combined with  
6 the substrate 12 integrally as shown in Fig. 6.

7 In the cutting process 40, the rim of combination of the  
8 three-dimensional molded layer 11 and the substrate 12 is trimmed and cut,  
9 thereby forming a three-dimensional molded blade 10 as shown in Fig. 7,  
10 wherein the three-dimensional molded blade 10 consists of the  
11 three-dimensional molded layer 11 and the substrate 12.

12 Accordingly, the molded layer 11 forms an arch-shaped structure on  
13 the surface of the substrate 12 as shown in Fig. 2, so that the molded blade 10  
14 has a greater structural support strength with a light weight, thereby decreasing  
15 consumption of rotational energy of the ceiling fan.

16 In addition, the molded blade 10 is manufactured by an automatic  
17 process without needing the manual work, so that the molded blade 10 can be  
18 produced at a higher speed with a higher quality.

19 Further, the molded blade 10 can be produced rapidly, easily and  
20 conveniently without needing the manual work, thereby decreasing costs of  
21 fabrication.

1           Further, the pattern of the molded layer 11 can be changed arbitrarily  
2 by variation the shape of the cavity 210 of the shaping mold 21, thereby  
3 enhancing aesthetic quality and variation of the molded blade 10.

4           While the preferred embodiment(s) of the present invention has been  
5 shown and described, it will be apparent to those skilled in the art that various  
6 modifications may be made in the embodiment(s) without departing from the  
7 spirit of the present invention. Such modifications are all within the scope of  
8 the present invention.